



# 2021

# PRODUCT GUIDE



[ITCAGRICULTURE.COM.AU](http://ITCAGRICULTURE.COM.AU)

02 6792 2069



**ABOUT**

# **GROUND ENGAGING TOOLS & WEAR PARTS FOR MINING, CIVIL, & AGRICULTURE APPLICATIONS**

INCORPORATED IN 2001 ITC STARTED AS A TUNGSTEN OVERLAY SUPPLIER TO THE NORTH WEST NSW AGRICULTURAL MARKET FOR THEIR GROUND ENGAGING TOOLS. SEEING AN OPPORTUNITY TO SUPPLY THE ACTUAL WEAR PARTS RESULTED IN ITC DEVELOPING THEIR OWN MINIMUM TILLAGE PARTS, CLOSELY FOLLOWED BY THE IMPORTATION OF EARTHMOVING AND

MINING PARTS FOR THE RESPECTIVE INDUSTRIES. ITC HAVE A PROUD HISTORY OF PRODUCT DEVELOPMENT THROUGH CONTINUED RESEARCH AND DEVELOPMENT IN THEIR PRODUCTS. THROUGH THEIR SPECIALISED, IN-HOUSE APPLICATION OF TUNGSTEN OVERLAY TO GROUND ENGAGING TOOLS AND WEAR PARTS, ITC HAVE BECOME LEADERS IN PRODUCT SUPERIORITY AND VALUE FOR MONEY.



# TUNGSTEN CARBIDE OVERLAY

TCO IS THE PROCESS OF APPLYING A SPECIAL TUNGSTEN GRIT MATERIAL TO THE GET SURFACE. WITH FIELD-TESTED RESULTS, OUR TUNGSTEN OVERLAY TECHNOLOGIES ARE ABLE TO EXTEND WEAR LIFE BY 3 TO 4 TIMES COMPARED TO REGULAR GET PARTS. WE SOURCE THE TUNGSTEN CARBIDE MATERIALS FROM THE HIGHEST QUALITY MANUFACTURES, WHICH ENSURE OUR CUSTOMERS ACHIEVE THE BEST RESULT. WITH OUR EXPERIENCE IN HARD-FACING, WE CAN ADVISE YOU THE BEST OPTIONS FOR YOUR GET REQUIREMENTS ACCORDINGLY.



# TABLE OF CONTENTS

---

<b>DISCS .....</b>	<b>5</b>
<b>COULTER DISCS .....</b>	<b>10</b>
<b>POINTS &amp; SWEEPS.....</b>	<b>13</b>
<b>U-BOLTS &amp; SHEAR PINS .....</b>	<b>18</b>
<b>ALABAMA SWEEPS &amp; FURROWERS.....</b>	<b>19</b>
<b>ROW CROP.....</b>	<b>19</b>
<b>GESSNER POINTS / TYNES .....</b>	<b>20</b>
<b>JOHN DEERE SEEDER BOOTS .....</b>	<b>20</b>
<b>FLEXI COIL BOOTS .....</b>	<b>20</b>
<b>JANKE POINTS .....</b>	<b>20</b>
<b>YEOMAN POINTS .....</b>	<b>20</b>
<b>AGRO PLOW .....</b>	<b>20</b>
<b>EXCEL POINTS .....</b>	<b>20</b>



# DISCS



## 13" DIAMETER - PLAIN



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
4150	3	P	24	No centre hole	5x7.1mm Dia	47.6mm	CS, SH, CNH SUGAR CANE PLANTER	2.0

## 16" DIAMETER - PLAIN/SCALLOPED



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
16002	4	P	38	27 & 30 SQ			JA, HB, MF	3.8
16006	4	S	38	27 & 30 SQ			JA, HB, MF	3.4

## 18" DIAMETER - SCALLOPED



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
18006	5	S	45	30 SQ			CSN, JA	6.7

## 20" DIAMETER - PLAIN



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
20011	4	P	51	27 & 30 SQ			JA, BNL, CN, HB, DH, SH, MF	6.1

## 20" DIAMETER - SCALLOPED



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
20012	4	S	51	27 & 30 SQ			JA, BNL, MF, CN, SH	5.6
20013	4	S	51	27 & 30 SQ FLATBACK			IH, MF	5.6
20018	5	S	51	27 & 30 SQ			JA, BNL, MF, CN, SH	7.2

## 22" DIAMETER – SCALLOPED



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
22160	4	S	85	27 & 30 SQ			JA	7
22040	5	S	60	39 & 41 SQ			JA, WY, BNL, CN, TW	8.8
22041	5	S	60	30 SQ			CN, SH, HB	8.8
22042	5	S	68	27 & 30 SQ FLATBACK			IH3-4, MF, CH	8.8
22051	6	S	60	70 RND	6x18.3 mm Dia	56.5 mm	CS, BABY G, & DOD	10.6
22052	6	S	60	30SQ			CH, SH	10.6
22055	6	S	60	70 RND	4 x 18.3mm Dia	68.5 mm	GRIZZLY GRUMPY, K-LINE	10.6

## 24" DIAMETER – FLUTED



MODEL	Thickness	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
24099 F	6	W	70	70 RND	4 x 18.3mm Dia	68.5 mm	"GRIZZLY GRUMPY, W/ Track Reno, K Line"	13.9
24100 F	6	W	70	30 SQ			SH, CN, BNL, HE	13.9
24101 F	6	W	70	39 & 41 SQ			IH, SH, CN, GR, JA, BNL, HUTCHMASTER	13.9
42102 F	6	W	70	54 & 60 SQ			IH 3-5	13.9

## 24" DIAMETER – SCALLOPED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
24072	5	S	70	30 SQ			SH, CN, HE	10.8
24092	5	S	80	30 SQ			SH, CN, IH, HB	10.8
24094	5	S	80	39 & 41 SQ			SH, HB, IH, BH, CN, JA, SH, TW	10.8
24074	6	S	70	30 SQ			SH, CN, HE	13.6
24099	6	S	80	70 RND	4 x 18.3mm Dia	68.5	GRIZZLY GRUMPY, K LINE SPEED TILLER	13.6
24100	6	S	80	30 SQ			SH, CN, BNL, HE	
24101	6	S	80	39 & 41 SQ			IH, SH, JA, CN, GR, BNL	13.6
24102	6	S	80	54 & 60 SQ			IH 3-5	13.6

## 24" DIAMETER – SCALLOPED (CONT.)



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
24103	6	S	80	70 RND	6 x 18.3mm Dia	56.5	CS, BABY G, & DOD	13.6
24106	6	S	80	46 RND			Miller, Delmade, SH, Baldan, S/ Flower	13.6
24107	6	S	80	100 RND	6 x 22mm Dia	92.5	GRIZZLY "S" SERIES	13.6
24109	6	S	70	39 SQ FLAT-BACK			IHC 596	13.6
24112	6	S	80	39 RND			UNABEAM	13.6

## 24" DIAMETER – PLAIN



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
24080	5	P	80	21 RND	6 x 13mm Dia CSK	82.5mm	SH, 5GP	11.1
24084	5	P	95	33 SQ			CH	11.1
24085	5	P	80	39 & 41 SQ			SH, HB, IH, BH, CN, JA	11.1
24086	5	P	80	25 RND	3 x 17mm Sq C/ Leaf	92mm	"CS, SERIES 4 (one way)"	11.1

## 26" DIAMETER – PLAIN



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
26119	5	P	100	33 SQ			CH	14.6
26121	5	P	100	39 & 41 SQ			IH, SH, JA, CN570, GR, SOVEREIGN	14.6
26122	5	P	100	21 RND	6 x 13mm Dia CSK	82.5mm	SH, 5GP	14.6
26164	6	P	100	21 RND	6 x 13mm Dia CSK	82.5mm	SH, 5GP	14.6

## 26" DIAMETER – FLUTED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
26137 F	6	W	90	70 RND	4 x 18.3mm Dia	68.5mm	GRIZZLY GRUMPY	15.6
26139 F	6	W	90	100 RND	6 x 22mm Dia	92.5mm	GRIZZLY "S" SERIES, BEL	15.6
26151 F	8	W	90	100 RND	6 x 22mm Dia	92.5mm	GRIZZLY "S" SERIES, BEL	20.8
26152 F	8	W	90	52 RND			EZY, STGR, C WIDE	20.8

# 26" DIAMETER – SCALLOPED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
26137	6	S	88	70 RND	4 x 18.3mm Dia	68.5 mm	GRIZZLY GRUMPY	15
26139	6	S	88	100 RND	6 x 22mm Dia	92.5 mm	GRIZZLY" S" SERIES, BEL	15
26140	6	S	88	78 RND	6 x 22mm Dia	95mm	BNL,CS,LTL,G,EN	15
26141	6	S	88	39 & 41 SQ			JA,GR,SH,BNL,CN670 & 730, HE	15
26142	6	S	70	39 & 41 SQ			TW, JA	15
26143	6	S	88	54 & 60 SQ			IH 3-5, SH700	15
26144	6	S	88	70 RND	6 x 18mm Dia	56.5 mm	CS, BABY G, & DOD	15
26146	6	S	88	46 RND			MILLER, DELMADE, SH, BALDAN	15
26160	6	S	100	30 & 33 SQ			JD, CN	15
26161	6	S	81	39 SQ FLAT-BACK			IH 596, 770	15
26151	8	S	88	100 RND	6 x 22mm Dia	92.5mm	GRIZZLY" S" SERIES,- BEL	19.8
26152	8	S	88	52 RND			EZY, STGR, C WIDE	
26153	8	S	88	78 RND	6 x 22mm Dia	95mm	BNL,CS, LTL, G, EN	19.8
26154	8	S	88	39 & 41 SQ			CN, JA, GR, HE	19.8
26155	8	S	100	58 RND			KEL	19.8
26162	8	S	81	39 SQ FLAT-BACK			IH 596, 770	19.8
26163	8	S	88	46 RND			MILLER, DELMADE, SH, BELDAN	19.8

# 28" DIAMETER – PLAIN



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
28165	6	P	110	32 SQ	4X13,5mm SQ CSK	115mm	CN, IH, BNL, HE	19.6



## 28" DIAMETER – FLUTED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
28168 F	6	W	105	100 RND	6 x 22mm Dia	92.5mm	GRIZZLY"S"SERIES	18.6
28170 F	6	W	105	78 RND	6 x 22mm Dia	95mm	BNL, EN	18.6
28169 F	8	W	105	100 RND	6 x 22mm Dia	92.5mm	GRIZZLY"S"SERIES, BEL	18.6
28178 F	6	W	105	52 RND			EZY,STGR, CW, MIL	18.6

## 28" DIAMETER – SCALLOPED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
28167	6	S	92	39 & 41 SQ			CN,SH,BNL,JA,HE	17.7
28168	6	S	110	100 RND	6 x 22mm Dia	92.5 mm	GRIZZLY"S"SERIES, BEL	17.7
28170	6	S	110	78 RND	6 x 22mm Dia	95mm	BNL, EN	17.7
28185	6	S	92	54 & 60 SQ			IH, 3-5, SH700	17.7
28179	6	S	92	39 SQ FLAT- BACK			IH, 770	17.7
28171	8	S	110	78 RND	6 x 22mm Dia	95mm	BNL, EN	24.7
28169	8	S	110	100 RND	6 x 22mm Dia	92.5 mm	GRIZZLY"S"SERIES, BEL	24.7
28175	8	S	92	39 & 41 SQ			CN,JA,HE,BNL	24.7
28177	8	S	92	46 RND			DELMUDE, BALDAN	24.7
28178	8	S	92	52 RND			EZY,STGR,CW,MIL	24.7
28179	8	S	92	39 SQ FLAT- BACK			IH, 770	24.7
28183	8	S	110	43 RND			TATU OFFSET	24.7
28269	10	S	104	100 RND	6 x 22mm Dia	92.5 mm	GRIZZLY	24.7

## 32" DIAMETER – SCALLOPED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
32190	8	S	122	45 SQ FLAT- BACK			IH780	30.6
32193	10	S	112	59 SQ / 62 RND			ALFM, 080, TNR, 620	39
32199	10	S	122	100 RND	6 x 22mm Dia	92.5mm	GRIZZLY"S"SERIES	39
32196	12	S	122	59 SQ / 62 RND			ALFM,080,TNR,620	50

## 36" DIAMETER – SCALLOPED



MODEL	Thickness (MM)	Type	Dish (mm)	Centre (mm)	Radial Holes	PCR	Common Application	Unit (KG)
36122	12	S	123	100 RND	6 x 22mm Dia	92.5mm	"GRIZZLY, Tiny'290&390"	63

# COULTER DISCS

## 11 1/4" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6100	4	DBL BEVEL	72 RND	5	9	48	C/S 470 Drill

## 13 1/2" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6336	3	DBL BEVEL	72 RND	5	9	48	C/S 470,8000 Drill

## 15" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6380	3	SINGLE BEVEL	30 RND	6	8	37.2	JD & KINZE PLANTERS

## 16" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6407	4	DBL BEVEL	64 RND	5	14	54	HT HOLDEN HUB
6424	4	SINGLE BEVEL	25 RND	6	7	36.5	MASON PLANTER/ EXCEL PLANTER
6426	4	SINGLE BEVEL	45 RND	4	10.5	38	EXCEL PLANTER
6430	4	SINGLE BEVEL	75 RND	5	13 SQ	54	EXCEL STUBBLE WARRIOR
6433	4	SINGLE BEVEL	75 RND	5	13.5	54	EXCEL STUBBLE WARRIOR
6434	4	SINGLE BEVEL	75 RND	5	13.5	54	EXCEL ST WARRIOR (Radial Holes 80 Deg. CSK)

# 18" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6440	4	12 WAVES	64 RND	5	14	54	HT HOLDEN HUB
6457	4	DBL BEVEL	64 RND	5	14	54	HT HOLDEN HUB YEOMANS
6473	4	50 RIPPLES	64 RND	5	14	54	HT HOLDEN HUB YEOMANS
6472	6	SINGLE BEVEL	64 RND	5	14	54	HT HOLDEN HUB
6480	5	SINGLE BEVEL	77 RND	4	10.3	55.85	JOHN DEERE & GRAYS PLANTERS
6481	5	SINGLE BEVEL	92.7 RND	4	15.8	63.5	BARTON DISC OPENERS (Flexicoil), BOSS
6482	6	SINGLE BEVEL	77 RND	4	10.3	55.85	JOHN DEERE, GRAYS & And INGERSOIL PLANTERS

# 20" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6522	6	DOUBLE BEVEL	64 RND	5	14	54	HT HOLDEN HUB
6523	6	SINGLE BEVEL	64 RND	5	14	54	JANKE, GESSNER ROOT- Cutter, Austill, HT Holden Hub

# 22" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
22726	6	single level	64 RND	5	14	54	JANKE, GESSNER, AUSTILL

# 26" DIAMETER



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6667	6	DOUBLE BEVEL	46 RND	4	18	82.5	HODGE
6668	6	DOUBLE BEVEL	52 RND	4	14	82.5	HODGE
6672	8	SINGLE BEVEL	108 RND	6	14	70	EXCEL

# 30" COULTER DISCS



MODEL	Thickness (MM)	Type	Centre Hole (mm)	Radial Holes	Bold Holes Diameter (mm)	"Holes PCR (mm)"	Application
6767	9	DOUBLE BEVEL	30 RND				BLANK
6776	9	DOUBLE BEVEL	51 RND	4 8	18 12.3	82.5 146	HODGE, BNL, P+H
6777	9	DOUBLE BEVEL	108 RND	6	14	70	EXCEL

# POINTS & SWEEPS

## POINTS & SWEEPS SW323

### SLIM WEDGE SERIES



KNOCK ON POINTS & SWEEPS FOR HEAVY DUTY CULTIVATORS, CHISEL PLOUGH & SCARIFIERS

Part number	Width (inches)	mm	Common Applications
ITC32309	9	8	Slim wedge sweeps for cultivators, air seeders & chisel ploughs with either 43, 47, 50 or 54 degree tyne angle. Suits Vibrashank, Flexi-Coil, Bourgault, Morris, J.D., Versatile, Gason, Leon, AFM, Horwood Bagshaw, Trashworker etc.
ITC23210	10	8	
ITC23211	11	8	
ITC23212	12	8	
ITC23214	14	8	

## DOUBLE BOLT HOLE CULTIVATORS & AIR SEEDERS

### PELICAN 47 DEGREES SWEEPS



BOLT ON POINTS & SWEEPS FOR HEAVY DUTY CULTIVATORS

Part number	Width (inches)	mm	Common Applications
ITC4778	7	8	Flexi-coil, Bourgault, H Bagshaw, Gason, Simplicity IH Vibrashank and machines with 47 deg. Tynes 2x Bolt holes on 44.5mm (1 3/4") centres. Use either 7/16" or 1/2" plough bolts.
ITC4798	9	8	
ITC4710	10	8	
ITC4712	12	8	
ITC4714	14	8	

## SW53 BOLT ON SWEEPS

SUIT MANY 3PL CULTIVATORS USING COIL TYNES



Part number	Width (inches)	mm	Common Applications
ITC53005	5	6	Ford Crown, Harvey, Gibbins, MF tiller, MF coil tynes & Agpoint coil tynes 2 x 7/16" bolt holes on 44.5mm to 51mm (1 3/4" to 2") centres Use 7/16" plough bolts.
ITC53006	6	6	
ITC53007	7	6	
ITC53008	8	6	
ITC53010	10	6	

# CULTIVATORS & COMBINES

## KNOCK ON/SLIP ON TO SUIT SINGLE BOLT HOLE CULTIVATOR TYNES



Marlow Seeding Points – ML1 Straight to Suit 41 or 43 Degree Tynes

Part number	Width (inches)	mm	Common Applications
ML10001	20	5	Seeding point - 20mm
ML10010	10	5	Lucerne point - NARROW

Marlow Cultivator Points - MR2 Series to Suit 45 Degree Tynes



Part number	Width (inches)	mm	Common Applications
ITCM2x2	2	5	Most combines & cultivators with fluted or Similar to International, Ackland
ITCM2x4	4	5	
ITCM2x5	5	5	
ITCM2x6	6	5	
ITCM2x7	7	5	
ITCM2x8	8	5	

Marlow Clips



Part number	Width (inches)	mm	Common Applications
MR21100	6	6	6mm Clip

Bolt-on Cultivator Points – Universal Fit



Part number	Width (inches)	mm	Common Applications
ITC 61 x 4	4	6	Gyral, Alfarm, Napier Trash Seeder, Napier 520 & 640 Cultivator, Agtech, Ford New Holland Combines, AFM180, Gason Cultimaster, Shearer, Ryan, H Bagshaw Fieldmaster, Symonds, IHC Spring Release
ITC 61 x 5	5	6	
ITC 61 x 6	6	6	
ITC 61 x 7	7	6	
ITC 61 x 8	8	6	

Bolt-on Cultivator Sweeps



Part number	Width (inches)	mm	Common Applications
ITC16108	8	6	Gyral, Alfarm, Napier Trash Seeder, Napier 520 & 640 Cultivator, Agtech, Ford New Holland Combines, AFM180, Gason Cultimaster, Shearer, Ryan, H Bagshaw Fieldmaster, Symonds, IHC Spring Release
ITC16109	9	6	
ITC16110	10	6	
ITC16112	12	6	

# SCARIFIERS

## BOLT-ON SCARIFIER POINTS



SC20 Series Bolt on Scarifier Points Universal Fit – No Tang

Part number	Width (inches)	mm	Common Applications
ITC 20 x 4	4	6	Universal fit scarifier point to suit Horwood Bagshaw, Chamberlain, John Deere, IHC, Shearer, Napier, Connor Shea and other scarifiers Use single 1/2" Cup head bolt
ITC 20 x 5	5	6	
ITC 20 x 6	6	6	
ITC 20 x 7	7	6	
ITC 20 x 8	8	6	
ITC 20 x 9	9	6	
ITC 20 x 10	10	6	



SW57A Series Bolt-on Scarifier Sweeps – Universal Fit

Part number	Width (inches)	mm	Common Applications
ITC 57010A	10	6	Scarifier Sweeps – fit IH., H.B. Symonds, MF, Ryan, Chamberlain & Shearer
ITC57012A	12	6	
ITC 57014A	14	6	



Key Hole Scarifier Points

Part number	Width (inches)	mm	Common Applications
ITC80001	1.5	6	Points to suit Connor-Shea Scarifiers with keyhole type point attachment - Use either a 1/2" x 1 1/2" long or 1/2" x 1 3/4" long plough bolts
ITC80008	8	6	
ITC80009	9	6	
ITC80010	10	6	

# CHISEL PLOUGHS

## BOLT ON CHISEL PLOUGH SWEEPS



### ITC43 Series Bolt-on Chisel Plough Sweeps 43 Degree Tyne

Part number	Width (inches)	mm	Common Applications
ITC4312	12	8	Morris, Taylorway, Allis Chalmers, Gason, Gyrat Penetrator, Hiniker, IHC 4700 - 2 x 1/2" bolt holes on 57mm (2 1/4") centres
ITC4314	14	8	
ITC4316	16	8	
ITC4318	18	8	



### ITC50 Series Bolt-on Chisel Plough Sweeps 50 Degree Tyne

Part number	Width (inches)	mm	Common Applications
ITC5008	8	8	Versatile, John Deere, Alfarm, Gason, Gessner, H Bagshaw, Yeomans, AFM, Hesston, Noble, Leon, Callow Big Rig, Bourgault, Flexi-Coil, Morris - 2 x 1/2" bolt holes @ 57mm (2 1/4") centres
ITC5010	10	8	
ITC5012	12	8	
ITC5014	14	8	
ITC5016	16	8	
ITC5018	18	8	



### ITC50 Series Bolt-on Flat Wing Chisel Plough Sweeps 50 Degree Tyne

Part number	Width (inches)	mm	Common Applications
ITC50022FW	22	8	Each Flexi-Coil, Orion, Hesston
ITC50026FW	26	8	Each Lely, AFM, Jet Stream, Versatile
ITC50030FW	30	8	Each 2 x 1/2" bolt holes @ 57mm (2 1/4") centres. Use 1/2" plough bolts



### ITC500G Series Bolt-on Sweeps to Suit Gessner Chisel Plough

Part number	Width (inches)	mm	Common Applications
ITC5012G	12	8	Gessner HD1200 Chisel Plough 2 x 5/8" bolt holes @ 2 1/4" (57mm) centres
ITC5014G	14	8	
ITC5016G	16	8	
ITC5018G	18	8	



# CHISEL PLOUGHS (CONT.)

## Bolt-on Chisel Plough Sweeps ITC 54 Series - Shearer Trashworker Sweeps



Part number	Width (inches)	mm	Common Applications
ITC5412	12	8	"2 x 9/16" P.B. bolt holes @ 76.2mm (3") centres Use special 9/16" trashworker plough bolts"
ITC5414	14	8	
ITC5416	16	8	
ITC5418	18	8	

## Reversible Chisel Points For Shearer Trashworker & Ecodraft



Part number	Width (inches)	mm	Common Applications
ITC00350-16	2	16	Suits Shearer Trashworker & Econodraft, Banana Farming Co - Multiworker
ITC00350-22	2	20	Use special 9/16" Trashworker plough bolts B6815

## Reversible Chisels For North American Style Chisel Ploughs



Part number	Width (inches)	mm	Common Applications
ITC21610-16	2	16	G.Hoeme, JD, Morris, Gason Hiniker, Versatile and many Nth. American style machines With 2 x 1/2" bolt holes at 57mm (2 1/4") centres
ITC21610-22	2	20	

## BOLT ON CHISEL PLOUGH SWEEPS

### Reversible Chisel For Coil Tynes

Part number	Width (inches)	mm	Common Applications
ITC54002	2	8mm	MF, Tiller, David Brown, 25 and 32mm coil tynes
ITC54205	2 1/2"	8mm	2 x 7/16" CSK bolt holes slotted 44 - 51mm (1 3/4"-2) centres
ITC00330	40mm	12mm	IH, Vibrashank and M.F. Use plough bolts
ITC00330B	40mm	16mm	2 x 7/16" CSK bolt holes slotted 50mm centres

### Reversible Chisel For Coil Tynes



Part number	Width (inches)	mm	Common Applications
ITC00681	3	20mm	2 x 1/2" Plough bolts @ both 51mm (2") and 112mm (4 1/2") centres (Suit Napier, Ford)

# U-BOLTS & SHEAR PINS

## U-BOLTS



Part Number	Inside Width (D)	Inside Length (Less Thread) A	Diameter	Thread Type	Bar Size	Thread Length B
UB353558	91mm	85mm	5/8"	UNC	3 1/2" x 3 1/2"	45mm
UB040458	102mm	105mm	5/8"	UNC	4" x 4"	50mm
UB040434	102mm	95mm	3/4"	UNC	4" x 4"	55mm
UB040634	102mm	145mm	3/4"	UNC	4" x 6"	55mm
UB060434	152mm	95mm	3/4"	UNC	6" x 4"	55mm
UB060658	152mm	145mm	5/8"	UNC	6" x 6"	45mm
UB060634	152mm	145mm	3/4"	UNC	6" x 6"	55mm
UB070758	180mm	230mm	5/8"	UNC	7 x 7"	55mm
UB070734	180mm	175mm	3/4"	UNC	7 x 7"	55mm
UB070778	180mm	181mm	7/8"	UNC	7 x 7"	51mm
UB080858	202mm	195mm	5/8"	UNC	8" x 8"	45mm
UB080878	202mm	195mm	7/8"	UNC	8" x 8"	51mm
UB080834	202mm	195mm	3/4"	UNC	8" x 8"	55mm

## SHEAR PINS

ALL SHEAR PINS SUPPLIED WITH RETAINING CLIPS



Part number	Diameter	Length (Between Grooves)	Common Applications
ITC061	25.4mm	61mm	Agroplow, Gessner, Keech, Bonel
ITC071	25.4mm	71mm	Agroplow
ITC095	25.4mm	95mm	Agroplow

# ROW CROP

## ALABAMA SWEEPS



Part number	Width Inches	Thickness (Mm)	Common Applications
ITC58118	18	8mm	Alabama high crown sweeps
ITC58124	24	8mm	Use ½" Plough bolts

## FURROWERS



Part number	Width Inches	Thickness (Mm)	Common Applications
ITC9312	12	6mm	Hole & slot or 3 hole available
ITC9315	15	6mm	High wing Lister furrower - 6mm thickness
ITC9318	18	6mm	Use ½" Plough bolts
ITC9319	22	6mm	
ITC00061			Furrower point. Use Cup head bolts

## GESSER POINTS / TYNES



Part number	Description	Applications
ITC011	GESSNER SHIN GUARD	Gessner
ITC011TC	SHIN GUARD COATED	Gessner
ITC003G	POINT PLAIN	Gessner
ITC003 GTC	TILED/HARD FACED	Gessner Point
SP061	SHEAR PIN	Gessner
ITC006	TYNE (HALF SHANK)	Gessner Half Tyne
ITC06TS	TYNE TOP STRAIGHT	Gessner
ITC006TA	TOP ANGLE	Gessner
FWCL	WEAR PLATES	Gessner
FWCR	WEAR PLATES	Gessner

## ITC NATIONAL - CAST APPLICATIONS - POINTS / TYNES



Part number	Description	Applications
R1024	POINT HARD FACED +TILED (Wombat)	Yeoman Point
HL24S	POINT	Grizzly Point
ITC036	POINT TILED	Janke Point
ITC036L	(NI HARD) LONG	Janke
ITC009	POINT	Excel Point
ITC050	POINT	MultiFarm/Banana
ITC025	POINT	Baker Boot
ITC037T	POINT	Mint T
ITC005T	POINT	DDP30T
ITC005TTC	POINT	DDP30T4
ITC030LS	POINT	DDP12LS
ITC012	POINT	DDP18WT
ITC012TC	POINT	HARD FACED
ITC008	POINT	FLEXI COIL BOOT
ITC098	POINT	JD SEEDER BOOT
ITC099	POINT	JD SEEDER BOOT
ITC014	POINT	FLEXI COIL POINT & TILES
ITC033	POINT	16mm POINT 13 TILES
ITC002	POINT	AGROPLOW POINT



**Agriculture**

**ITCAGRICULTURE.COM.AU**

**02 6792 2069**